

**NT22A-50M****21.5”****500Nits Open Frame Touch Signage**

## Key Feature

- 1920 × 1080 Resolution with 500nits brightness
- Built-In Speaker
- HDMI input port
- 10 Points Capacitive Touch
- Industrial grade components
- Open frame design for Embed Installation
- Mounting Guide Bracket

# Specification

## Display

Model	NT22A-50M
Screen Size (Diagonal)	21.5 inch
Native Resolution	1920 × 1080
Brightness	500 cd/m <sup>2</sup>
Contrast	1000:1
View Angle	178°(H) / 178°(V)
Display Color	16.7M
Color Gamut	73% NTSC
Life Time (Light Source)	30,000 Hrs (Min.)

## Touch

Touch Type	10 Points Capacitive Touch
Touch Method	Finger
Touch Accuracy	≤2mm
Touch Response Time	<4ms
Light Transmission	≥85%

## Interface

VGA	1(In)
DVI	1(In)
HDMI	1(In)
USB	1(In)
Touch USB	1(In)

## Product

Speakers	2 x 2W (8Ω)
----------	-------------

## Power

Power supply	AC110-240V(50/60HZ)
Power consumption	40W

## Environment

Operation temperature	0°C~40°C
Operation humidity	10%~80% RH

# Specification

## Physical

Color	GRAY or BLACK
Body Dimension	523(H) x 315(V) x 56.7(D)mm
Set Weight	6.7Kg
Package Dimension	610(H) x 423(V) x 152(D)mm
Package Weight	8.7 Kg
Mounting Holes	350 × 200

## Dimension Drawing

