

NT55A-80M**55''****800nits Open Frame Touch Monitor**

Key Feature

- 3840 × 2160 4K Resolution with 800nits brightness
- Built-In Speakers
- 10 Points Capacitive Touch
- HDMI input port
- Industrial grade components
- Open Frame Design for embedded installation
- Mounting Guide Bracket

Specification

Display

| | |
|--------------------------|-----------------------|
| Model | NT55A-80M |
| Screen Size (Diagonal) | 55 inch |
| Native Resolution | 3840 × 2160 |
| Brightness | 800 cd/m ² |
| Contrast | 1200:1 |
| View Angle | 178°(H) / 178°(V) |
| Display Color | 1.07B |
| Color Gamut | 74% |
| Life Time (Light Source) | 50,000 Hrs |

Touch

| | |
|---------------------|----------------------------|
| Touch Type | 10 Points Capacitive Touch |
| Touch Method | Finger |
| Touch Accuracy | ≤2mm |
| Touch Response Time | <4ms |
| Light Transmission | ≥85% |

Interface

| | |
|------------|--|
| A/V Input | USB x1, HDMI x1, DVI x1, VGA x1, CVBS x1, Audio x1, RS232 x1 |
| A/V Output | Audio x1, RS232 x1 |

Product

| | |
|----------|-------------|
| Speakers | 2 x 5W (8Ω) |
|----------|-------------|

Power

| | |
|-------------------|----------------------|
| Power supply | AC 100-240V(50/60HZ) |
| Power consumption | TBD |

Environment

| | |
|-----------------------|------------|
| Operation temperature | 0°C~40°C |
| Operation humidity | 10%~80% RH |

Specification

Physical

| | |
|-------------------|--------------------------------|
| Color | GRAY or BLACK |
| Body Dimension | 1288(H) x 771.5(V) x 72.2(D)mm |
| Set Weight | TBD |
| Package Dimension | TBD |
| Package Weight | TBD |
| Mounting Holes | 500x400 |

Dimension Drawing

